

NO-A116 873

ADMIRALTY MARINE TECHNOLOGY ESTABLISHMENT DUNFERMLIN--ETC P/O 20/11
CLOSED FORM SOLUTION FOR THE BENDING STRESSES IN RING - STIFFEN--ETC(U)
DEC 81 D J CREZWELL

UNCLASSIFIED


ANTE(S)/R81756

DRIC-BR-82767

NL

1 11
2000

END
DATE
FILMED
17-82
DTIC



UNLIMITED

1

BR82767

REPORT AMTE(S) R81756

COPY No 22

AMTE(S) R 81756



ADMIRALTY MARINE TECHNOLOGY ESTABLISHMENT

AD A116073

CLOSED FORM SOLUTION FOR THE BENDING
STRESSES IN RING - STIFFENED SHELLS
WITH SHAPE IMPERFECTIONS (U)

D. J. Creswell

DTIC
ELECTE
JUN 25 1982
S B D

AMTE (Dunfermline)
St. Leonard's Hill
DUNFERMLINE Fife KY11 5PW

DECEMBER 1981

UNLIMITED

DTIC FILE COPY

82 06 24 09Z

AMTE(S) R81756

CLOSED FORM SOLUTION FOR THE BENDING STRESSES IN
RING-STIFFENED SHELLS WITH SHAPE IMPERFECTIONS(U)

BY

D J CRESWELL

Summary (U)

A closed form solution for the displacements and stresses of a slightly non-circular, ring-stiffened shell is derived rigorously from thin shell theory. The solution may be implemented on programmable pocket calculators, providing an accurate, but easy to use, method for predicting bending stresses.

This document is the property of Her Majesty's Government and Crown copyright is reserved. Requests for permission to publish its contents outside official circles should be addressed to the Issuing Authority.

AMTE (Dunfermline)
St Leonard's Hill
DUNFERMLINE Fife KY11 5PW

December 1981

CONTENTS

	<u>Page No</u>
TITLE	1
DISTRIBUTION	3
NOTATION	4-5
INTRODUCTION	6
THEORY	6-15
NUMERICAL EXAMPLES	15
CONCLUSIONS	15
REFERENCES 1-6	16
TABLES 1-5	17-21
APPENDIX	22-28
FIGURE 1	
ABSTRACT CARDS	

DISTRIBUTIONCopy No

1	DAMTE, Teddington
2	DGRA/CS(RN), Main Building, London
3	DES Washington
4	CS(R)2e(Navy), Bourne Avenue, Hayes
5-26	DRIC, Orpington, Kent
27-29	DG Ships, Section 124, Bath
30	DPT 32, Bath
31	DAUWE, Portland
32	Vickers Ltd, Barrow-in-Furness (Attn of Mr Burford)
33	SOC, BNS, Washington
34	Professor G D Galletly, Liverpool University
35-38	AMTE (Dunfermline) Internal Loan
39-48	Spares



Accession For	
NTIS	<input checked="" type="checkbox"/>
DTIC	<input type="checkbox"/>
Unrestricted	<input type="checkbox"/>
Availability Codes	
Dist	Special
A	

NOTATION

d^r	displacement from rest (generic form)
d^i	initial imperfection (generic form)
\bar{d}	axisymmetric displacement (generic form)
E	Young's Modulus
ν	Poisson's ratio
R	shell radius
h	shell thickness
L	shell section length
z	distance from shell mid-surface (positive inwards)
e	distance from shell mid-surface to frame centroid (positive for internal frames)
$e_\theta, e_x, \gamma_{x\theta}$	circumferential, axial and shear strains respectively
A_F	frame area
x	axial position; as a subscript denotes differentiation with respect to x when used in conjunction with $u, v, w,$ w^i
θ	circumferential co-ordinate; as a subscript denotes differentiation with respect to θ when used in con- junction with u, v, w, w^i
u_I, v_I, w_I	eigen vector amplitudes associated with I^{th} basis function in the expansion of axial, circumferential and radial bifurcation displacements, respectively
$u(x,\theta), v(x,\theta), w(x,\theta)$	axial, circumferential and radial bifurcation displace- ments, respectively. (x , and θ often omitted). w positive inwards
$w^i(x,\theta)$	the radial out-of-circularity at x and θ . (x and θ often omitted)
w_x^i, w_θ^i	derivatives of w^i with respect to x and θ , respectively
$\bar{u}(x)$	axial pre-buckling displacement
$\bar{w}(x)$	radial pre-buckling displacement
$\bar{w}_x(x)$	pre-buckling rotation

N_i	upper limit to the number of basis functions required in the expansion of bifurcation displacements
n	number of circumferential waves
e_{oc}	maximum departure from mean circle
\underline{x}	displacement vector
p	lateral pressure (positive external)
P	axial pressure (positive external)
I_{oc}	wave number of imperfection shape, $e_{oc} \sin I_{oc} \pi x/L$
N_f	number of frames
N_s	number of frame spaces
L_f	frame spacing
b	width of faying flange, or web thickness
R_g	centroidal radius of frame
A_{m2}	second moment of area of frame, for in-plane bending
A	frame area
I	second moment of area
) in the Kendrick Frame expressions (Appendix)

CLOSED FORM SOLUTION FOR THE BENDING STRESSES IN RING-STIFFENED SHELLS WITH SHAPE IMPERFECTIONS

INTRODUCTION

An important consideration in the design of externally pressurised cylindrical shells is the allowance for the shape imperfections which inevitably occur during manufacture. Components of out-of-circularity which approximate to critical buckling mode shapes are considerably exaggerated as the applied pressure approaches the corresponding buckling pressure. Frame stresses may exceed the material yield strength, precipitating failure by one of several mechanisms.

2. Many methods are available for finding the buckling pressures of the perfect ring-stiffened shell, and while frame stresses may be found with simplifying assumptions concerning the way mode shapes will develop (1, 2, 3)*, comparatively few analyses exist which allow a completely satisfactory direct solution to the bending stresses.

3. The purpose of the analysis presented in this paper is to provide a closed form solution for the displacements and frame bending stresses in a nearly circular, uniformly framed, ring-stiffened cylindrical shell. The method is based rigorously on thin-shell theory, but is nevertheless simple enough to allow calculations to be made on a programmable pocket calculator.

THEORY

4. Kendrick has shown that the strains in a slightly non-circular shell may be written as follows (1):

$$e_{\theta} = (v_{\theta} - w)/R + (w_{\theta}^2 + u_{\theta}^2 - 2wv_{\theta})/2R^2 + (w_{\theta}^i w_{\theta} - w^i w)/R^2$$

$$e_x = u_x + (1/2)(w_x^2 + v_x^2) + w_x^i w_x$$

$$\gamma_x = u_{\theta}/R + v_x \quad [1]$$

The strains contain quadratic products of the displacements, u , v , w and the imperfections w^i . From equations such as [1], a set of linear equations may be derived, the solution of which yields the displacements and stresses in the shell. An outline of the derivation is given below in general terms, applying to any set of strain expressions. A specific derivation, using the original Kendrick expressions (1) is given in the Appendix.

5. An expression for the strain of shell and frames is written in terms of the displacements from rest (d^r) and the initial imperfection (d^i). Parameters d^r and d^i represent in generic form terms of the following type:

*() = References on page 16

d^r : w^r, v^r, u^r and their derivatives with respect to axial position x and circumferential position θ

d^i : w^i, w_θ^i, w_x^i

where w, v and u are respectively radial, circumferential and axial displacements.

The strain expression contains terms proportional to d^r , $(d^r)^2$ and $d^r d^i$, the exact form of the expression depending to some extent on the basic formulation used: the Novazhilov formulation uses a Cartesian co-ordinate system; the method used by Kendrick uses cylindrical co-ordinates.

6. The total potential energy is given by the following expression

$$U_T = U_s + U_f - W$$

where the contributions from shell (U_s), frames (U_f) and external load (W) may be expressed as

$$U_s = \int_0^{2\pi} \int_0^L u_s(x, \theta) dx d\theta \quad . \quad [2]$$

$$U_f = \int_0^{2\pi} \sum_{\text{frames}} u_f(x, \theta) d\theta \quad . \quad [3]$$

$$W = \int_0^{2\pi} \int_0^L w(x, \theta) dx d\theta \quad . \quad [4]$$

The shell and frame energy densities (u_s and u_f respectively) contain the following types of terms up to cubic order in d^r :

$$(d^r)^2 \quad (d^r)^3 \quad (d^r)^2 d^i \quad (d^r)^3 d^i \quad .$$

The load potential term has terms in:

$$d^r \quad (d^r)^2 \quad \text{and} \quad d^r d^i$$

7. Total displacements (d^r) are expressed as the sum of primary displacements (\bar{d}) and bifurcation or buckling displacements (d):

$$d^r = \bar{d} + d \quad . \quad [5]$$

The following terms, of less than cubic order in d or \bar{d} , are then present in U_T :

$$\begin{array}{cccc}
 \bar{d} & d & & \\
 \bar{d}^2 & \bar{d}d & d^2 & \\
 \bar{d}^3 & \bar{d}^2d & \bar{d}d^2 & d^3 \\
 d^i \bar{d}^2 & d^i \bar{d}d & d^i d^2 & \\
 d^i \bar{d}^3 & d^i \bar{d}^2 d & d^i \bar{d}d^2 & d^i d^3
 \end{array}$$

8. The primary displacements (\bar{d}) at any desired pressure p are evaluated first, including if necessary the effects due to an axisymmetric imperfection. It is assumed that non axisymmetric imperfections are sufficiently small so that \bar{d} may be considered to be axisymmetric. The bifurcation displacements d are found by minimising U_T . Bifurcation displacements are assumed to be sufficiently small to enable coupling between different lobar modes to be ignored. The bifurcation mode shape is considered therefore to be a pure Fourier mode. With the simplifying assumptions concerning pre-buckling and buckling displacements, only five sets of terms need be considered:

From the strain energy densities:

1. d^2 (Eh/R)
2. $\bar{d}d$ (Eh/R^2)
3. $\bar{d}d^i$ (Eh/R^2)
4. $d^i d^2$ (Eh/R^2)

and from the external work:

5. pd^2

where p is the applied pressure.

The typical order of magnitude of coefficients corresponding to each type is indicated in brackets. Terms 1 and 4 are independent of external load (p). Terms 2, 3 and 5 are directly dependent on p . The coefficients of type 4 terms are such that the contributions of the terms are smaller than the contributions from type 1 terms, by the ratio d^i/R . The effect of type 4 terms is to couple different lobar modes for large displacements. Provided the level of out-of-circularity is small in relation to the radius, and the gradient of the imperfection surface not too rapidly varying in the x -direction, type 4 terms may be ignored, maintaining compatibility with the assumption that the development of different lobar modes occurs independently.

9. Bifurcation displacements are represented in terms of Fourier functions.

$$\begin{aligned}
 u(x, \theta) &= \cos n\theta \sum_{I=1}^{N_I} u_I \cos I\pi x/L \\
 v(x, \theta) &= \sin n\theta \sum_{I=1}^{N_I} v_I \sin I\pi x/L \\
 w(x, \theta) &= \cos n\theta \sum_{I=1}^{N_I} w_I \sin I\pi x/L
 \end{aligned}
 \tag{6}$$

On minimisation of U_T with respect to the amplitudes u_I, v_I, w_I , for $I = 1$ to N_I and scaling to a non-dimensional form, the following matrix problem arises

$$M \underline{x} = \underline{c} \tag{7}$$

where $M = A + \psi B$

$$\psi = pR(1 - \nu^2) / Eh \tag{8}$$

Matrix A contains coefficients of type 1 terms (d^2). Matrix B comprises coefficients of terms from types 2 and 5. The vector \underline{c} derives from group 3 terms, and \underline{x} is the displacement vector whose terms are the amplitudes of the Fourier functions at any pressure p :

$$\underline{x}^T = (u_1 \ v_1 \ w_1 \ \dots \ u_I \ v_I \ w_I \ \dots \ u_{N_I} \ v_{N_I} \ w_{N_I}) \tag{9}$$

10. For the perfectly axisymmetric structure ($\underline{c} = 0$) the matrix problem of equation [7] reverts to the standard buckling eigen value problem. Matrices A and B are identical to the buckling matrices.

11. Prebuckling distributions required for the B matrix and \underline{c} vector have, in this paper, been calculated as follows. The axisymmetric radial deformation of a frame in a uniformly framed, ring-stiffened cylinder, under unit hydrostatic load is given precisely by the following expression (4, 5)

$$\bar{w}_f = R^2 (1 - \nu/2) / \{ Eh [1 + A / (bh + 2Nh/\alpha)] \} \tag{10}$$

where

$$\begin{aligned}
 A &= A_f (R/R_g)^2 \\
 \nu &= [3(1 - \nu^2)]^{1/4} / \sqrt{Rh} \\
 N &= (\cosh \alpha L' - \cos \alpha L') / (\sinh \alpha L' + \sin \alpha L') \\
 L' &= L_f - b
 \end{aligned}$$

To conserve radial load, the net circumferential stress in the shell must satisfy the following equation:

$$\bar{\sigma}_{\theta}^{sh} L_f = RL_f - EA_f \bar{w}_f / R_g \quad [11]$$

The longitudinal pre-stress $\bar{\sigma}_x^{sh}$ is given by

$$\bar{\sigma}_x^{sh} = -R/2h \quad [12]$$

The axisymmetric circumferential strain (\bar{e}_{θ}^{sh}) and the axial strain (\bar{u}_x^{sh}) in the shell are:

$$\bar{e}_{\theta}^{sh} = E^{-1} \left[\bar{\sigma}_{\theta}^{sh} - \nu R/2h \right] \quad [13]$$

$$\bar{u}_x^{sh} = E^{-1} \left[\nu \bar{\sigma}_{\theta}^{sh} - R/2h \right] \quad [14]$$

for the chosen sign convention, pressure positive external, displacements positive inwards.

12. The matrix M may now be defined very simply (details in Appendix). Shell and frame components are considered separately,

$$M = M_s + M_f .$$

For a ring-stiffened cylinder of uniform shell thickness the shell matrices are banded tri-diagonally,

$$\begin{aligned} M_s(IU, IU) &= m_0^{uu} + I^2 m_2^{uu} \\ M_s(IU, IV) &= I m_1^{uv} \\ M_s(IU, IW) &= I m_1^{uw} + I^3 m_3^{uw} \\ M_s(IV, IV) &= m_0^{vv} + I^2 m_2^{vv} \\ M_s(IV, IW) &= m_0^{vw} + I^2 m_2^{vw} \\ M_s(IW, IW) &= m_0^{ww} + I^2 m_2^{ww} + I^4 m_4^{ww} \end{aligned} \quad [15]$$

where

$$\begin{aligned} IU &= 3I - 2 \\ IV &= 3I - 1 \\ IW &= 3I \end{aligned} \quad I = 1, 2, \dots, N_I \quad [16]$$

to be compatible with the displacement vector definition, equation [9].

Expressions for m_o^{uu} etc specific to the Kendrick formulation are given in the Appendix.

13. Satisfactory solution of overall buckling problems may be obtained if out-of-plane bending stiffness of frames is ignored in both A and B matrices (3). The frame terms of the M matrix then contain neither x-derivatives nor terms in axial displacement u.

$$\begin{aligned} M_f (IV, JV) &= f^v S(I, J) \\ M_f (IV, JW) &= f^{vw} S(I, J) \\ M_f (IW, JW) &= f^w S(I, J) \end{aligned} \quad [17]$$

where

$$S(I, J) = (2/N_s) \sum_{i=1}^{N_f} \sin(I\pi x_i/L) \sin(J\pi x_i/L) \quad [18]$$

14. The \underline{c} vector may be similarly decomposed into shell and frame terms

$$\underline{c} = \underline{c}_s + \underline{c}_f$$

If the imperfection is of the form $e_{oc} \cos n\theta \sin(I_{oc}\pi x/L)$ the shell components of the \underline{c} vector may be written as follows (equations [13] and [23] of the Appendix):

$$\begin{aligned} c_s (IU) &= I c_1^u \delta_{II_{oc}} \\ c_s (IV) &= c_o^v \delta_{II_{oc}} \\ c_s (IW) &= \left[c_o^w + c_2^w I^2 \right] \delta_{II_{oc}} \end{aligned} \quad [19]$$

The frame terms are given by

$$\begin{aligned} c_f (IV) &= c_f^v c(I) \\ c_f (IW) &= c_f^w c(I) \end{aligned} \quad [20]$$

where

$$c(I) = (2/N_s) \sum_{i=1}^{N_f} \sin(I\pi x_i/L) \sin(I_{oc}\pi x_i/L) \quad [21]$$

15. For a uniformly framed structure (identical, uniformly spaced frames) only sinusoidal components obeying the following relationship for some integral value of K are coupled (3):

$$I = \left(\frac{1}{2}\right) \left\{ \left[1 - (-1)^{I'} \right] \left[(I' - 1)N_s + K \right] \pm \left[1 + (-1)^{I'} \right] \left[I'N_s - K \right] \right\}$$

[22]

for $I' = 1, 2, 3, \dots, N_I$

Functions satisfying equation [22] with either " " or "-" in the centre provide a complete orthogonal set. Selecting the "-" option, it may be shown straightforwardly that

$$S(I, J) = 1 \quad [23]$$

for all I, J satisfying equation [22]. Only the long wavelength shapes will be required,

$$e_{oc} \sin(K\pi x/L) \quad \text{for } K = 1, 2, 3, \dots,$$

representing the fundamental modal components of equation [22]. If $I_{oc} = K$, $K \leq N_f$, then

$$c(I) = 1 \quad [24]$$

for all I satisfying equation [22]. It follows immediately that the fundamental matrix, equation [7], may be stated in the following form:

$$\begin{aligned} M_s(IU, IV)u_I + M_s(IV, IV)v_I + M_s(IV, IW)w_I + f^v \Sigma v_I + f^{vw} \Sigma w_I \\ = c_0^v \delta_{II_{oc}} + c_f^v \end{aligned} \quad [25]$$

$$\begin{aligned} M_s(IU, IW)u_I + M_s(IV, IW)v_I + M_s(IW, IW)w_I + f^{vw} \Sigma v_I + f^w \Sigma w_I \\ = (c_0^w + c_2^w I^2) \delta_{II_{oc}} + c_f^w \end{aligned} \quad [26]$$

$$M_s(IU, IU)u_I + M_s(IU, IV)v_I + M_s(IU, IW)w_I = I c_1^u \delta_{II_{oc}} \quad [27]$$

the summations being performed for a set of I given by [22].

16. From equation [27], u_I can be written explicitly in terms of v_I and w_I , allowing the matrix dimension to be reduced by a factor of 2/3:

$$\begin{aligned} S^v(I)v_I + S^{vw}(I)w_I &= c^v(I) - f^v \Sigma v_I - f^{vw} \Sigma w_I \\ S^{vw}(I)v_I + S^w(I)w_I &= c^w(I) - f^{vw} \Sigma v_I - f^w \Sigma w_I \end{aligned} \quad [28]$$

where

$$\begin{aligned} s^v(I) &= M_s(IV, IV) - M_s(IU, IV)^2 / M_s(IU, IU) \\ s^{vw}(I) &= M_s(IV, IW) - M_s(IU, IV) M_s(IU, IW) / M_s(IU, IU) \end{aligned} \quad [29]$$

$$s^w(I) = M_s(IW, IW) - M_s(IU, IW)^2 / M_s(IU, IU)$$

$$c^v(I) = c_f^v + c_{sh}^v \quad [30]$$

$$c^w(I) = c_f^w + c_{sh}^w$$

$$c_{sh}^v = \delta_{II_{oc}} \left[c_0^v - I c_1^u M_s(IU, IV) / M_s(IU, IU) \right] \quad [31]$$

$$c_{sh}^w = \delta_{II_{oc}} \left[c_0^w + c_2^w I^2 - I c_1^u M_s(IU, IW) / M_s(IU, IU) \right]$$

17. Equations [28] show that v_I and w_I , for any I , can be expressed in terms of summations over v_I and w_I :

$$\begin{aligned} v(I) &= s^w(I) \left[c^v(I) - \eta \right] - s^{vw}(I) \left[c^w(I) - \xi \right] \\ w(I) &= s^v(I) \left[c^w(I) - \xi \right] - s^{vw}(I) \left[c^v(I) - \eta \right] \end{aligned} \quad [32]$$

where

$$\begin{aligned} \eta &= f^v \Sigma^v + f^{vw} \Sigma^w \\ \xi &= f^{vw} \Sigma^v + f^w \Sigma^w \end{aligned} \quad [33]$$

Σ^v and Σ^w denoting Σv_I and Σw_I respectively,

$$\begin{aligned} s^v(I) &= S^v(I) / D(I) \\ s^{vw}(I) &= S^{vw}(I) / D(I) \\ s^w(I) &= S^w(I) / D(I) \\ D(I) &= S^v(I) S^w(I) - S^{vw}(I)^2 \end{aligned} \quad [34]$$

18. Substituting equations [32] into equations [28], it may be seen that

$$\begin{aligned} \Sigma^V = & \{ [1 + \bar{s}_v f^W - \bar{s}_{vw} f^{vw}] c_1 - [\bar{s}_w f^{vw} - \bar{s}_{vw} f^W] c_2 \} / \\ & \{ [1 + \bar{s}_w f^V - \bar{s}_{vw} f^{vw}] [1 + \bar{s}_v f^W - \bar{s}_{vw} f^{vw}] - \\ & [\bar{s}_v f^{vw} - \bar{s}_{vw} f^V] [\bar{s}_w f^{vw} - \bar{s}_{vw} f^W] \} \end{aligned} \quad [35]$$

$$\Sigma^W = [c_1 - (1 + \bar{s}_w f^V - \bar{s}_{vw} f^{vw}) \Sigma^V] / (\bar{s}_w f^{vw} - \bar{s}_{vw} f^W) \quad [36]$$

where

$$\bar{s}_v = \Sigma s^V(I) \quad \bar{s}_{vw} = \Sigma s^{vw}(I) \quad \bar{s}_w = \Sigma s^W(I) \quad [37]$$

$$c_1 = \bar{s}_w c_f^V - \bar{s}_{vw} c_f^W + s^W(1) c_{sh}^V - s^{vw}(1) c_{sh}^W \quad [38]$$

$$c_2 = \bar{s}_v c_f^W - \bar{s}_{vw} c_f^V + s^V(1) c_{sh}^W - s^{vw}(1) c_{sh}^V$$

19. Equations [32] to [38] represent the closed form solution for the circumferential (v) and radial (w) displacements of a hydrostatically loaded, slightly non-circular, uniformly framed, ring-stiffened cylinder, with shape imperfection $e_{oc} \sin(K\pi x/L) \cos(n\theta)$. Equations [35] to [38] may be evaluated directly in terms of known shell and frame coefficients (equations [21] and [25] of Appendix).

20. Equations [32] give $v(I)$ and $w(I)$ from which the shell displacements at any position x using equations [6] and [22]. In this derivation the central sign of equation [22] has been taken to be minus. If the 'plus' option is used the final expressions take on the slightly modified, but numerically equivalent, form given in (3).

21. The stresses, at position z on a frame section, are given by the following expression

$$\sigma(z) = \sigma_{ax}(z) + \sigma_b(z) \quad [39]$$

where the axisymmetric stress $\sigma_{ax}(z)$ is given by

$$\sigma_{ax}(z) = E \bar{w}_f / (R - S_i z), \quad [40]$$

and the bending stress $\sigma_b(z)$ is given by

$$\sigma_b(z) = (E/R) [n v(x) - w(x) + (z/R) (n^2 - 1) w(x)] \quad [41]$$

NUMERICAL EXAMPLES

22. Displacements and stresses have been evaluated on the two rather different structures given in Table 1.

23. Displacements and stresses in the closely frame-spaced submersible structure are given in Tables 2-4. The predictions of closed form and matrix method are almost identical. The closed form method is particularly useful for convergence tests (Table 4).

24. In the widely frame-spaced VAC type structure severe mixed-mode effect occurs for $n > 2$. The closed form method provides therefore a very simple method of allowing for mixed mode effect in ring-stiffened cylinders. Displacements and stresses predicted by closed form and matrix methods agree almost exactly (Figure 1, Table 5).

CONCLUSIONS

25. By means of analytical simplification, it is possible to derive rigorously from thin-shell-theory, a closed form expression for the bending stresses in a uniformly framed ring-stiffened cylinder with non-axisymmetric shape imperfection.

26. The analytic method has been implemented on a programmable pocket calculator and results are shown to agree with the predictions of more usual matrix methods which require quite large computers for accurate solution.

27. It is felt that the 'closed form' method provides a useful means of checking the prediction of:

- a. more sophisticated methods, such as finite difference and finite element, and
- b. approximate methods used in design codes, such as the effective breadth approach of BS5500.

The method is particularly appropriate for carrying out convergence studies to assess the fine-ness of mesh required in more sophisticated analyses.

REFERENCES

1. S Kendrick: "The Deformation Under External Pressure of Nearly Circular Cylindrical Shells with Evenly Spaced Equal Strength Nearly Circular Ring Frames". NCRE Report, R259, October 1953.
2. P M Roxburgh: "The Deformation of Nearly Circular Stiffened Cylinders". NCRE Report, R472, September 1962.
3. D J Creswell, G D Galletly: "Externally Pressurized Shells". Int Conf Buckling of Shells in Offshore Structures, April 1981, held at Imperial College, London.
4. L B Wilson: "The Deformation under Uniform Pressure of a Circular Cylindrical Shell Supported by Equally Spaced Circular Ring Frames". NCRE Report, R337, A, B and C, December 1956.
5. "The Stress Analysis of Pressure Vessels and Pressure Vessel Components", Chapter 9. Edited by S S Gill, Pergamon Press, 1970.

NOTE: Not all of the References referred to above are automatically available to the general public.

TABLE 1

CASE 1 - PV4 SUBMERSIBLE

19 equispaced frames

R = 2000 mm

h = 17.879 mm

L = 12000 mm

E = 207000 N/mm²

v = 0.3

d = 180.92 mm

h_w = 9.046 mm

f = 90.46 mm

h_f = 15.07 mm

INTERNAL

CASE 2 - PV4 VAC TYPE

1 central frame

R = 2500 mm

h = 20 mm

L = 14000 mm

E = 207000 N/mm²

v = 0.3

d = 192 mm

h_w = 12 mm

f = 0

h_f = 0

INTERNAL

R shell radius

h shell thickness

L shell length

E Young's modulus

v Poisson's ratio

d web depth

h_w web thickness

f flange width

h_f flange thickness

TABLE 2

α	v Closed form	v Matrix	w Closed form	w Matrix	$ v_B^{1-} $ Closed form	$ v_B^{1-} $ Matrix	$ v_B^{ms} $ Closed form	$ v_B^{ms} $ Matrix
0.01	0.0439	0.0329	1.3647	1.3645	35.18	34.03	8.36	8.15
0.1	1.2720	1.2509	2.7036	2.6560	69.43	68.41	16.52	16.10
0.2	1.8685	1.8065	3.9720	3.9020	102.09	100.51	24.27	23.65
0.3	2.4295	2.3781	5.1426	5.0519	132.16	130.17	31.43	30.61
0.4	2.9107	2.8609	6.1686	6.0775	159.01	156.54	37.81	36.82
0.5	3.3301	3.2782	7.0782	6.9534	181.43	179.10	43.26	42.13
0.6	3.6876	3.6049	7.7956	7.6581	200.37	197.25	47.64	46.40
0.7	3.9145	3.8479	8.3209	8.1742	213.67	210.55	50.85	49.52
0.8	4.0656	3.9961	8.6414	8.4830	222.11	218.66	52.81	51.43
0.9	4.1460	4.0459	8.7432	8.5448	224.89	221.36	53.47	52.07

174 Summable $n = 2$ displacements and bending stresses at 3 N/mm^2 for shape $20 \cos 26 \sin \pi x/L$. Comparison of results from the closed form method, evaluated on a pocket calculator ($N = 5$) and a matrix method (10×10 , $\text{IfAC} = 0$).

TABLE 3

x/L	v Closed Form	v Matrix	w Closed Form	w Matrix	$ \sigma_b^{fl} $ Closed Form	$ \sigma_b^{fl} $ Matrix	$ \sigma_b^{ms} $ Closed Form	$ \sigma_b^{ms} $ Matrix
0.05	0.3137	0.3096	0.6660	0.6563	17.19	17.05	3.99	3.84
0.1	0.5967	0.5890	1.2669	1.2484	32.70	32.43	7.60	7.30
0.15	0.8213	0.8107	1.7437	1.7183	45.01	44.63	10.46	10.05
0.2	0.9655	0.9530	2.0500	2.0200	52.91	52.47	12.30	11.81
0.25	1.0152	1.0020	2.1553	2.1239	55.64	55.17	12.93	12.42
0.3	0.9655	0.9530	2.0500	2.0200	52.91	52.47	12.30	11.81
0.35	0.8213	0.8107	1.7437	1.7183	45.01	44.64	10.46	10.05
0.4	0.5967	0.5890	1.2669	1.2484	32.70	32.43	7.60	7.30
0.45	0.3137	0.3096	0.6660	0.6563	17.19	17.05	3.99	3.84
0.5	0	$0.36 \cdot 10^{-8}$	0	$0.68 \cdot 10^{-8}$	0	0	0	0

PV4 Submersible $n = 2$ displacements and bending stresses at 3 N/mm^2 for shape $20 \cos 2\theta \sin 2\pi x/L$. Comparison of results from the closed form method ($M = 5$) and a matrix method (30×30 matrix, IFAC = 0).

TABLE 4

M	N	V	W	σ_b^{fl}	σ_{TOT}^{fl}
1	6	3.854	8.060	220	417.0
2	12	4.080	8.653	224	421.5
3	18	4.106	8.723	225	422.0
5	30	4.116	8.749	225	423.0

PV4 Submersible $n = 2$, shape $20 \cos 2\theta \sin \pi x/L$.

Convergence test: M convergence parameter,

N equivalent (IFAC = 0) matrix size.

Pressure 3 N/mm^2 .

TABLE 5FRAME DISPLACEMENTS - PV4 VAC TYPE STRUCTUREpressure = 0.3 N/mm^2 $e_{oc} = 25 \text{ mm}$ $I_{oc} = 1$

	n = 2	n = 3	n = 4	n = 5	n = 6
<u>Circumferential Displacements (v)</u>					
Closed Form	1.3725	5.0266	2.4920	1.1397	0.44280
Matrix	1.3724	5.0292	2.5007	1.1502	0.44616
<u>Radial Displacements (w)</u>					
Closed Form	2.7460	15.470	10.412	6.0950	2.9730
Matrix	2.7449	15.475	10.444	6.1474	2.9940

APPENDIX

In equations [1] e_θ , e_x , $\gamma_{x\theta}$ are respectively the circumferential, axial and shear strains. The displacements w , v , etc are measured from rest, the superscript "r" being omitted for convenience. The extensional shell energy is then given by the standard plane-stress, thin shell expression:

$$U_e = \int_0^{2\pi} \int_0^L \left[ERh/2 (1 - \nu^2) \right] \{ e_\theta^2 + e_x^2 + 2\nu e_\theta e_x + (1/2)(1 - \nu) \gamma_{x\theta}^2 \} d\theta dx \quad [A1]$$

2. The following expression for the shell bending strain energy was used by Kendrick (6):

$$U_b = \int_0^{2\pi} \int_0^L \left[ERhk/2 (1 - \nu^2) \right] \{ R^2 w_{xx}^2 + (w_{\theta\theta} + w)^2/R^2 + (1/2)(1 - \nu)(w_{x\theta} - u_\theta/a)^2 + (3/2)(1 - \nu)(v_x + w_{x\theta})^2 + 2\nu w_{xx} (w_{\theta\theta} + v_\theta) + 2Ru_x w_{xx} \} dx d\theta \quad [A2]$$

where $k = h^2/12R^2$. The shell energy contribution $U_s = U_e + U_b$. Frame extensional strains are expressed in terms of the mid-shell strain e_θ and the change of curvature due to in-plane bending, giving the following expression for the extensional frame energy F_e ,

$$F_e = \sum_{r=1}^{N_f} (EAR/2) \int_0^{2\pi} \{ e_\theta - (w_{\theta\theta} + w)(e/R^2) \}^2 d\theta \quad [A3]$$

3. Frame bending energy is given by:

$$F_b = \sum_{r=1}^{N_f} (EI/2R^3) \int_0^{2\pi} (w_{\theta\theta} + w)^2 d\theta \quad [A4]$$

4. The total frame energy $U_f = F_e + F_b$. The work done by external load on an initially imperfect cylinder is found to be given by the following expression:

$$W = (p/2) \int_0^{2\pi} \int_0^L \{ 2Rw - 2w^i w - w^2 + 2R(w^i + w)(u_x + v_\theta/a) - Ru_x v_\theta \} d\theta dx + (PR^2/2) \int_0^{2\pi} \int_0^L -u_x dx d\theta \quad [A5]$$

5. In all the expressions given above the superscript "r" denoting displacements from rest has been omitted. On making the transformation:

$$u^r(x, \theta) = \bar{u}(x) + u(x, \theta)$$

$$v^r(x, \theta) = v(x, \theta) \quad [A6]$$

$$w^r(x, \theta) = \bar{w}(x) + w(x, \theta)$$

the total potential energy U_T is found to be given by the following expression:

$$U_T = U_A + U_B + U_C \quad [A7]$$

where

$$U_A = \int_0^{2\pi} \int_0^L \left[EhR/2 (1 - \nu^2) \right] \{ u_x^2 + (v_\theta - w)^2/R^2 + 2\nu u_x (v_\theta - w)/R + (1/2)(1 - \nu)(u_\theta/R + v_x)^2 + k \left[R^2 w_{xx}^2 + (w_{\theta\theta} + w)^2/R^2 + (1/2)(1 - \nu)(w_{x\theta} - u_\theta/R)^2 + (3/2)(1 - \nu)(v_x + w_{x\theta})^2 + 2\nu w_{xx} (w_{\theta\theta} + v_\theta) + 2Ru_x w_{xx} \right] \} d\theta dx + \sum_{r=1}^{N_f} (EAR/2) \int_0^{2\pi} \{ [(w_{\theta\theta} + w)(e/R^2) + (w - v_\theta)/R]^2 + (I/R^4 A)(w_{\theta\theta} + w)^2 \} d\theta \quad [A8]$$

$$\begin{aligned}
U_B = & \int_0^{2\pi} \int_0^L \left[\frac{Eh}{2R^2}(1 - v^2) \right] \left\{ \bar{w} \left[-2v_\theta^2 - u_\theta^2 - w_\theta^2 + 4wv_\theta - \right. \right. \\
& R^2 v (w_x^2 + v_x^2) - 2Rv u_x v_\theta \left. \right] + \bar{u}_x \left[R^3 (v_x^2 + w_x^2) + \right. \\
& Rv (u_\theta^2 + w_\theta^2 - 2wv_\theta) \left. \right] + \\
& \bar{w}_x \left[2R^3 u_x w_x - 2vR^2 w_x (w - v_\theta) \right] \left. \right\} d\theta dx + \quad [A9] \\
& \sum_{r=1}^{N_f} (EA/2R^2) \bar{w} \int_0^{2\pi} \left\{ -(1 + e/R) u_\theta^2 - 2v_\theta^2 - (1 + e/R) w_\theta^2 + \right. \\
& 4(1 + e/R) wv_\theta + (2e/R) w_{\theta\theta} v_\theta \left. \right\} d\theta + (p/2) \int_0^{2\pi} \int_0^L \\
& \left\{ w^2 - 2w (v_\theta + Ru_x) + Ru_x v_\theta \right\} d\theta dx
\end{aligned}$$

$$\begin{aligned}
U_C = & \int_0^{2\pi} \int_0^L \left[\frac{Eh}{2R^2}(1 - v^2) \right] \left\{ \bar{w} \left[-2vRu_x w^i - 2v_\theta w^i + 4ww^i - 2w_\theta w_\theta^i - \right. \right. \\
& 2R^2 v w_x w_x^i \left. \right] + \bar{u}_x \left[-2Rv w w^i + 2Rv w_\theta w_\theta^i + 2R^3 w_x w_x^i \right] + \\
& \bar{w}_x \left[2R^2 v (v_\theta - w) w_x^i + 2R^3 u_x w_x^i \right] \left. \right\} d\theta dx + \quad [A10] \\
& \sum_{r=1}^{N_f} (EA/2R^2) \bar{w} \int_0^{2\pi} \left\{ -2v_\theta w^i + 4(1 + e/R) w w^i - \right. \\
& 2(1 + e/R) w_\theta w_\theta^i + (2e/R) w_{\theta\theta} w_\theta^i \left. \right\} d\theta + \\
& p \int_0^{2\pi} \int_0^L w^i (w - v_\theta - Ru_x) d\theta dx .
\end{aligned}$$

Terms proportional to the end loads (P) do not appear explicitly in the final expressions. Effects due to end loads are transferred through \bar{w} , \bar{u}_x and \bar{w}_x .

6. On minimization of the energy expressions, the A and B matrices and the c-vector may be written as follows:

$$A_S(IU, IU) = n^2(1+k)(1-v)/2 + I\lambda^2$$

$$A_S(IU, IV) = -nI\lambda(1+v)/2$$

$$A_S(IU, IW) = vI\lambda - n^2(1-v)kI\lambda/2 + k(I\lambda)^3$$

[A11]

$$A_S(IV, IV) = n^2 + (1-v)(1+3k)(I\lambda)^2/2$$

$$A_S(IV, IW) = -n \left[1 + (3-v)k(I\lambda)^2/2 \right]$$

$$A_S(IW, IW) = (1+k) + n^2k \left[n^2 - 2 + 2(I\lambda)^2 \right] + k(I\lambda)^4$$

$$B_S(IU, IU) = -n^2 b_s \bar{s}_\theta$$

$$B_S(IU, IV) = -nI\lambda/2 + n b_s v I \bar{e}_\theta^{sh}$$

$$B_S(IU, IW) = I\lambda$$

[A12]

$$B_S(IV, IV) = b_s \bar{s}_x (I\lambda)^2 - 2n^2 b_s \bar{e}_\theta^{sh}$$

$$B_S(IV, IW) = -n \left[1 - 2b_s \bar{e}_\theta^{sh} + b_s v \bar{u}_x^{sh} \right]$$

$$B_S(IW, IW) = 1 + b_s \left[(I\lambda)^2 \bar{s}_x - n^2 \bar{s}_\theta \right]$$

$$C_S(IU) = \psi e_{oc} I\lambda \left[1 + b_s v \bar{e}_\theta^{sh} \right] \delta_{II_{oc}}$$

$$C_S(IV) = -\psi e_{oc} n \left[1 + b_s \bar{e}_\theta^{sh} \right] \delta_{II_{oc}}$$

[A13]

$$C_S(IW) = \psi e_{oc} \left[1 + b_s \left\{ (2 - n^2) \bar{e}_\theta^{sh} + v(n^2 - 1) \bar{u}_x^{sh} + \bar{s}_x (I\lambda)^2 \right\} \right] \delta_{II_{oc}}$$

$$A_f(IV, JV) = n^2 f S(I, J)$$

$$A_f(IV, JW) = A_f(IW, JV) = -nf \left[1 - (n^2 - 1)e_r \right] S(I, J) \quad [A14]$$

$$A_f(IW, JW) = \left\{ f \left[(1 + e_r)^2 - 2n^2 e_r + n^2 (n^2 - 2)e_r^2 \right] + g(n^2 - 1)^2 \right\} S(I, J)$$

$$B_f(IV, JV) = 2n^2 b_f S(I, J)$$

$$B_f(IV, JW) = B_f(IW, JV) = -nb_f \left[2(1 + e_r) - n^2 e_r \right] S(I, J) \quad [A15]$$

$$B_f(IW, JW) = n^2 b_f (1 + e_r) S(I, J)$$

$$C_f(IV) = -\psi n c_f C(I)$$

[A16]

$$C_f(IW) = -\psi c_f \left[2(n^2 - 1)e_r + (n^2 - 2) \right] C(I)$$

where:-

$$IU = 3I - 2$$

$$JU = 3J - 2$$

$$IV = 3I - 1$$

$$JV = 3J - 1$$

[A17]

$$IW = 3I$$

$$JW = 3J$$

$$k = h^2/12R^2 \quad \lambda = \pi R/L \quad b_s = Eh/R(1 - \nu^2) \quad f = A_f N_s (1 - \nu^2)/hL$$

[A18]

$$g = A_{m2} N_s (1 - \nu^2)/hLR^2 \quad e_r = e/R \quad b_f = -EA_f \bar{w}_f N_s / R^2 L \quad c_f = -e_{oc} b_f$$

$$S(I, J) = (2/N_s) \sum_{i=1}^{N_f} \sin(I\pi x_i/L) \sin(J\pi x_i/L)$$

[A19]

$$C(I) = (2/N_s) \sum_{i=1}^{N_f} \sin(I\pi x_i/L) \sin(I_{oc} \pi x_i/L)$$

[A20]

7. Calculations are simplified if matrix M is cast in the form of equation [15] with m_o^{uu} etc defined as follows:

$$m_o^{uu} = n^2(1+k)(1-v)/2 - \psi n^2 b_s \bar{s}_\theta$$

$$m_2^{uu} = \lambda^2$$

$$m_1^{uv} = -n\lambda(1+v)/2 + \psi \left[b_s v \lambda n \bar{e}_\theta^{sh} - n\lambda/2 \right]$$

$$m_1^{uw} = v\lambda - n^2(1-v)k\lambda/2 + \psi\lambda$$

$$m_3^{uw} = k\lambda^3$$

$$m_o^{vv} = n^2 - \psi 2n^2 b_s \bar{e}_\theta^{sh}$$

[A21]

$$m_2^{vv} = (1-v)(1+3k)\lambda^2/2 + \psi \bar{s}_x \lambda^2 b_s$$

$$m_o^{vw} = -n - \psi n \left[1 - 2b_s \bar{e}_\theta^{sh} + b_s v \bar{u}_x^{sh} \right]$$

$$m_2^{vw} = -n(3-v)k\lambda^2/2$$

$$m_o^{ww} = (1+k) + kn^2(n^2-2) + \psi \left[1 - n^2 b_s \bar{s}_\theta \right]$$

$$m_2^{ww} = 2n^2 k \lambda^2 + \psi b_s \lambda^2 \bar{s}_x$$

$$m_4^{ww} = k\lambda^4$$

where:-

$$\bar{s}_\theta = \bar{\sigma}_\theta^{sh} (1-v^2)/E$$

[A22]

$$\bar{s}_x = \bar{\sigma}_x^{sh} (1-v^2)/E$$

8. With reference to equations [30] and [31], the c-vector coefficients appropriate to the Kendrick expressions are as follows:

$$c_1^u = -\psi e_{oc} \lambda \left[1 + b_s v \bar{e}_\theta^{sh} \right]$$

$$c_o^v = \psi e_{oc} n \left[1 + b_s \bar{e}_\theta^{sh} \right]$$

[A23]

$$c_o^w = -\psi e_{oc} \left[1 + b_s \{ (2 - n^2) \bar{e}_\theta^{sh} + v(n^2 - 1) \bar{u}_x^{sh} \} \right]$$

$$c_2^w = -\psi e_{oc} \bar{s}_x \lambda^2 b_s$$

$$c_f^v = \psi n c_f$$

[A24]

$$c_f^w = \psi c_f \left[2(n^2 - 1) e_r + (n^2 - 2) \right]$$

9. Frame coefficients f^v , f^{vw} and f^w are given by:

$$f^v = n^2 \left[f + \psi 2b_f \right]$$

$$f^{vw} = -n \left[f \{ 1 - (n^2 - 1) e_r \} + \psi b_f \{ 2(1 + e_r) - n^2 e_r \} \right]$$

[A25]

$$f^w = f \left[(1 + e_r)^2 - 2n^2 e_r + n^2 (n^2 - 2) e_r^2 \right] + g(n^2 - 1)^2 + \psi b_f n^2 (1 + e_r)$$




VAC TYPE STRUCTURE

$e_{oc} = 25 \text{ mm}$ $I_{oc} = 1$

$P = 0.3 \text{ N/mm}^2$

----- N124 D CLOSED FORM

● N124 D MATRIX SOLUTION



UNLIMITED

FIGURE 1

UNLIMITED

AMTE(S) R 81756

DOCUMENT CONTROL SHEET

(Notes on completion overleaf)

Overall security classification of sheet UNCLASSIFIED

(As far as possible this sheet should contain only unclassified information. If it is necessary to enter classified information, the box concerned must be marked to indicate the classification eg (R), (C) or (S).)

1. DRIC Reference (if known)	2. Originator's Reference AMTE(S)/R81756	3. Agency Reference	4. Report Security Classification UNLIMITED
5. Originator's Code (if known)	6. Originator (Corporate Author) Name and Location Admiralty Marine Technology Establishment St Leonard's Hill, Dunfermline, Fife, KY11 5PW		
5a. Sponsoring Agency's Code (if known)	6a. Sponsoring Agency (Contract Authority) Name and Location		
7. Title CLOSED FORM SOLUTION FOR THE BENDING STRESSES IN RING-STIFFENED SHELLS WITH SHAPE IMPERFECTIONS			
7a. Title in Foreign Language (in the case of translations)			
7b. Presented at (for conference papers). Title, place and date of conference			
8. Author 1, Surname, initials CRESWELL, D J	9a. Author 2	9b. Authors 3, 4...	10. Date pp ref 12.81 33 6
11. Contract Number	12. Period	13. Project	14. Other References
15. Distribution statement Distribution controlled by MOD Technical Policy Authority, Research Area Leader 1, OS AMTE Dunfermline			
Descriptors (or keywords) Ring Stiffened Cylinders Imperfect Shells Shell Theory Hydrostatic Loading			
Summary A closed form solution for the displacements and stresses of a slightly non-circular, ring-stiffened shell is derived rigorously from thin shell theory. The solution may be implemented on programmable pocket calculators, providing an accurate, but easy to use, method for predicting bending stresses.			

NOTES ON COMPLETION OF DOCUMENT CONTROL SHEET

This Document Process Sheet is designed specifically for MOD reports and reports produced by Contractors.

Boxes marked* below need be completed only if the information is readily available.

- *1. DRIC reference: Enter DRIC reference (BR number) if one has been assigned.
2. Originator's Reference: Enter the report number by which the document is identified by the originator of the report, in the form in which it appears on the cover.
3. Agency reference: Enter reference number allocated by sponsoring agency (contract authority) in the case of contract reports.
4. Report Security Classification: Enter security classification or marking which limits the circulation of the report, or enter UNLIMITED when this applies.
- *5. Originator's Code: Code number for the DRIC-standardised form of the entry appearing in Box 6.
- *5a. Sponsoring Agency's Code: Code number for the DRIC-standardised form of the entry appearing in Box 6a.
6. Originator (corporate author): Enter name and location of the organisation preparing the report.
- 6a. Sponsoring Agency (Contract Authority): Enter the name of the monitoring MOD Branch or Establishment in the case of Contractor's reports. If an MOD report covers work funded by an outside agency, enter the name of that agency.
7. Title: Enter the complete report title in capital letters but omitting initial definite or indefinite articles. If the report covers a specific period, enter this after the title, eg (1.1.1972-31.3.1972).
- 7a. Title in Foreign Language: In the case of translations, enter the foreign language title (transliterated if necessary) and the translated English title in Box 7.
- 7b. Conference Papers: If 7 is the title of a paper presented at a Conference, or a Conference proceedings, enter the Conference Title, where it was held and the date.
8. Author 1: Enter the name of the first author, followed by his initials.
- 9a. Author 2: Enter the name of the second author, followed by his initials.
- 9b. Authors 3,4...: Enter third and following authors' names.
10. Date: Enter the month (in figures) and the year of the report (Dec., 1969 is written 12.1969). If the report is undated but a period covered by the report is indicated, enter the date at the end of the period. pp.ref. Enter the inclusive number of pages in the report containing information, i.e. including appendices, tables and illustrations, and the total number of references cited.
11. Contract Number: Enter the number of the contract or grant under which the report was written.
12. Period: (always associated with the Contract Number). Only to be used for reports covering a specific period, e.g. quarterly, annual or final reports. Enter QR-1, AR, FR, as appropriate.
13. Project: Enter project name or number.
14. Other Reference: Enter any reference, other than those in Boxes 2 or 3, by which the report may be identified.
15. Distribution statement. Enter any limitations on the distribution of the document. If distribution is limited to particular groups eg MOD, MOD and its Contractors, etc. it should be stated. If the distribution is the responsibility of another authority eg a HQ Directorate (Technical Policy Authority) enter "Distribution controlled by MOD Technical Policy Authority". Enter "via DRIC" after "Authority" where appropriate and name the Technical Policy Authority if possible.

Descriptors: Any number of descriptors (or key-words) can be entered. If selected from a published thesaurus, eg The Thesaurus of Engineering and Scientific Terms (TEST), this should be indicated.

Abstract: The abstract should preferably not exceed 150 words, i.e. it can be considerably shorter than the Abstract to be provided on the Title Page of the Report. Information available in the report title need not be included in the abstract.

<p>AMTE(S)/R81756</p> <p>UNLIMITED</p> <p>CLOSED FORM SOLUTION FOR THE BENDING STRESSES IN RING-STIFFENED SHELLS WITH SHAPE IMPERFECTIONS by D J Creswell, 1981</p> <p>A closed form solution for the displacements and stresses of a slightly non-circular, ring-stiffened shell is derived rigorously from thin shell theory. The solution may be implemented on programmable pocket calculators, providing an accurate, but easy to use, method for predicting bending stresses.</p>	<p><u>SUBJECT INDEX</u></p> <p>Ring Stiffened Cylinders Imperfect Shells Shell Theory Hydrostatic Loading</p>	<p>AMTE(S)/R81756</p> <p>UNLIMITED</p> <p>CLOSED FORM SOLUTION FOR THE BENDING STRESSES IN RING-STIFFENED SHELLS WITH SHAPE IMPERFECTIONS by D J Creswell, 1981</p> <p>A closed form solution for the displacements and stresses of a slightly non-circular, ring-stiffened shell is derived rigorously from thin shell theory. The solution may be implemented on programmable pocket calculators, providing an accurate, but easy to use, method for predicting bending stresses.</p>	<p><u>SUBJECT INDEX</u></p> <p>Ring Stiffened Cylinders Imperfect Shells Shell Theory Hydrostatic Loading</p>
<p>AMTE(S)/R81756</p> <p>UNLIMITED</p> <p>CLOSED FORM SOLUTION FOR THE BENDING STRESSES IN RING-STIFFENED SHELLS WITH SHAPE IMPERFECTIONS by D J Creswell, 1981</p> <p>A closed form solution for the displacements and stresses of a slightly non-circular, ring-stiffened shell is derived rigorously from thin shell theory. The solution may be implemented on programmable pocket calculators, providing an accurate, but easy to use, method for predicting bending stresses.</p>	<p><u>SUBJECT INDEX</u></p> <p>Ring Stiffened Cylinders Imperfect Shells Shell Theory Hydrostatic Loading</p>	<p>AMTE(S)/R81756</p> <p>UNLIMITED</p> <p>CLOSED FORM SOLUTION FOR THE BENDING STRESSES IN RING-STIFFENED SHELLS WITH SHAPE IMPERFECTIONS by D J Creswell, 1981</p> <p>A closed form solution for the displacements and stresses of a slightly non-circular, ring-stiffened shell is derived rigorously from thin shell theory. The solution may be implemented on programmable pocket calculators, providing an accurate, but easy to use, method for predicting bending stresses.</p>	<p><u>SUBJECT INDEX</u></p> <p>Ring Stiffened Cylinders Imperfect Shells Shell Theory Hydrostatic Loading</p>

